
DS SERIES AIR-COOLED CONDENSING UNITS





Mueller® Air-Cooled Condensing Units

DS Series Air-Cooled Condensing Units Are Chillingly Effective

Mueller® DS series large horsepower air-cooled condensing units are designed and manufactured for the vigorous demands of either milk cooling or chilled water applications.

Paul Mueller Company air-cooled condensing units are available with 15 to 40 hp in 230- or 460-volt models.

Features and Benefits


- Liquid receiver with relief valve.
- Inlet and outlet service valves.
- High-pressure safety valve.
- Low-pressure operating control.
- Crankcase heater.
- Compressor contactor.
- · Separate subcooling circuit.
- Head pressure valves.
- Single unloader on 15- to 40-hp models.
- Main power disconnect.
- Control circuit transformer (460-volt units).
- Direct-drive condenser fans.
- Fan motor thermal protection.

- Pressure fan cycle control.
- Removable access panels.
- Weatherproof electrical panel.
- Hinged control panel access.
- Vibration isolation under compressor.
- Suction and discharge vibrasorber.
- Electronic oil pressure control.
- Service run/pump-down switch.
- Accumulator heat exchanger (factory installed).
- Fan motor contactor.
- A low ambient heated receiver kit for use when units are subject to normal ambient temperatures 30°F or below is available as an option.

| Mueller Air-Cooled Condensing Unit Specifications | | | | | | | | | | | | |
|---|------------------------------|----------------------------|-----|-----|------|--------------------------------|-----|------------------|-------------------|-------------------------------|--|--|
| Model No. | Comp 208-230/3 RLA/LRA | ressor 460/3 RLA/LRA | Qty | HP | | Fan Motor Amperage 230/3 | | Conne Suction | ections Liquid | Receiver Capacity R-507 | | |
| DS15H2 | 59.6/275 | 29.0/138 | 2 | 1.5 | 9.6 | 9.2 | 4.6 | 15⁄8″ | 7/8" | 123 lbs. | | |
| DS20H2 | 66.0/308 | 33.0/154 | 2 | 1.5 | 9.6 | 9.2 | 4.6 | 15⁄8″ | 7/8" | 123 lbs. | | |
| DS25H2 | 82.2/428 | 41.1/214 | 3 | 1.5 | 14.4 | 13.8 | 6.9 | 21/8" | 11/8" | 188 lbs. | | |
| DS30H2 | 94.0/470 | 47.0/235 | 3 | 1.5 | 14.4 | 13.8 | 6.9 | 21/8" | 1½" | 188 lbs. | | |
| DS35H2 | 107.0/565 | 53.5/283 | 4 | 1.5 | 19.2 | 18.4 | 9.2 | 21/8" | 1½" | 188 lbs. | | |
| DS40H2 | 142.0/594 | 71.0/297 | 4 | 1.5 | 19.2 | 18.4 | 9.2 | 21/8" | 11/8" | 188 lbs. | | |

Note: Chiller capacities at 20°F evaporator, 95°F ambient. Receiver capacity at 90% full.

Mueller Air-Cooled Condensing Unit Dimensions



| | Mueller Air-Cooled Condensing Unit Dimensions | | | | | | | | | |
|-----------|---|-------|--------|--------------------------------|--|--|--|--|--|--|
| Model No. | A — Length | Width | Height | Approximate Shipping Weight | | | | | | |
| DS15H2 | 170.7" | 44.5" | 55.5" | 1,680 lbs. | | | | | | |
| DS20H2 | 170.7" | 44.5" | 55.5" | 1,760 lbs. | | | | | | |
| DS25H2 | 225.7" | 44.5" | 55.5" | 1,950 lbs. | | | | | | |
| DS30H2 | 225.7" | 44.5" | 55.5" | 2,160 lbs. | | | | | | |
| DS35H2 | 280.7" | 44.5" | 55.5" | 2,770 lbs. | | | | | | |
| DS40H2 | 280.7" | 44.5" | 55.5" | 2,870 lbs. | | | | | | |

Visit <u>dfe.paulmueller.com</u> to see all of our *COOL* products!



1600 West Phelps Street • Springfield, Missouri 65802, U.S.A. DFE Sales: 888-645-5826 • Phone: 417-575-9000 • 800-MUELLER Fax: 417-575-9887 • 800-436-2466 • dairyfarm@paulmueller.com

©1998-2014 Paul Mueller Company MC-273-3